

MATERIAL SAFETY DATA SHEET
 May be used to comply with OSHA's Hazard
 Communication Standard, 29 CFR 1910.1200. Standard
 must be consulted for specific requirements.

U.S. Department of Labor
 Occupational Safety and Health Administration
 (Non-Mandatory Form)
 Form Approved
 OMB No. 1218-0072

IDENTITY (as Used on Label and List) 225-250 Veribest White Stamping Powder CK-7	Note: Blank spaces are not permitted. If any item is not applicable or no information is available, the space must be marked to indicate that.
---	--

Section I

Manufacturer's name COLONIAL TAILORS CHALK	Emergency Telephone Number None
Address (Number, Street, City, State and ZIP Code) 181 Market St Santa Rosa Beach, FL 32459	Telephone Number for Information
	Date Prepared 01-01-2014
	Signature of Preparer (optional) NA

Section II—Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity, Common Name(s))	OSHA PEL	ACGI H TLV	Other Limits Recommended	% (optional)
Quartz (MAX 2%)	2.5 mg M³			
BaSo4 - Barium sulfate	5 mg M³			
ZnS - Zinc sulfate	5 mg M³			
Rosin	5 mg M³			

Section III—Physical/Chemical Characteristics

Boiling Point	NA	Specific Gravity (H2O = 1)	4.2
Vapor Pressure (mm Hg)	NA	Melting Point	NA
Vapor Density (AIR = 1)	NA	Evaporation Rate (Butyl Acetate = 1)	NA
Solubility in Water	INSOLUABLE.		
Appearance and Odor	SLIGHT ODOR. WHITE POWDER.		

Section IV—Fire and Explosion Hazard Data

Flash Point (Method Used) NA	Flammable Limits: NA	LEL NA	UEL NA
--	--------------------------------	------------------	------------------

Extinguishing Media **DRY CHEMICAL CO2**
 Special Fire Fighting Procedures **AVOID USING WATER IN FIGHTING FIRE AS IT WILL CAUSE THE LIQUIFIED ROSIN TO FOAM AND SPLATTER**

Unusual Fire and Explosion Hazards **THE HOT ROSIN WILL GIVE OFF ACRID FUMES**

Section V—Reactivity Data			
Stability	Unstable		Conditions to Avoid
	Stable	X	STABLE. NONE.
Incompatibility (Materials to Avoid)		CONTACT WITH STRONG OXIDIZING AGENT	
Hazardous Decomposition or Byproducts		H2S	
Hazardous Polymerization	May Occur		Conditions to Avoid
	Will Not Occur	X	STABLE. NONE.
Section VI—Health Hazard Data			
Route(s) of Entry	Inhalation?	YES.	Skin? NO Ingestion? YES
Health Hazards (Acute and Chronic)			
ACUTE: RESPIRATORY. CHRONIC: SILICOSIS			
PRIMARY ROUTE OF ENTRY - INHALATION			
Carcinogenicity	NTP?	NO	IARC Monographs? NO OSHA Regulated? NO
Signs and Symptoms of Exposure:			
EXTREME DUSTY CONDITIONS			
Medical Conditions Generally Aggravated by Exposure: NA			
Emergency and First Aid Procedures			
WASH SKIN; FLUSH EYES WITH WATER			
Section VII—Precautions for Safe Handling and Use			
Steps to Be Taken in Case Material Is Released or Spilled			
IF POWDER IS SPILLED, SWEEP UP. IF MOLTEN MATERIAL IS SPILLED, ALLOW TO COOL, THEN SCRAPE UP.			
Waste Disposal Method			
DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS			
Precautions to Be Taken in Handling and Storing			
KEEP AWAY FROM HEAT OR FLAME			
Other Precautions			
PRODUCT IS SUSCEPTIBLE TO SPONTANEOUS IGNITION IN AIR, ESPECIALLY AT ELEVATED TEMPERATURES.			
Section VII—Control Measures			
Respiratory Protection (Specify Type)			
APPROPRIATE PROTECTIVE FILTER MASK			
Ventilation	Local Exhaust	IF NEEDED FOR DUST	Special NA
	Mechanical (General)	ADEQUATE TO KEEP BELOW TLV	Other VENT TO COLLECTOR
Protective Gloves	ADVISABLE	Eye Protection	SAFETY GOGGLES
Other Protective Clothing or Equipment		NA	
Work/Hygienic Practices MAINTAIN WALKING/WORKING SURFACE IN AS DUST-FREE CONDITIONS AS PRACTICABLE.			